



SRP9180

## SRP9180 Portable Radio Professionals' Choice

The SRP9180 has been designed to meet the exacting and demanding needs of mission critical users. Coupled with the functionality and flexibility that only Xmode can deliver, this is the radio to meet current and future needs. The flexibility and reliability of the SRP9180 will meet the challenges of demanding environments.

### Features

- ▶ Unique Xmode software and configuration upgradability, allowing operation on analogue, MPT1327 trunking, P25 conventional and P25 trunking systems.
- ▶ Ruggedized robust construction for demanding field use.
- ▶ Bright, easy to read display with ergonomic radio controls for operator convenience.
- ▶ IP67 ingress protection against dust and water immersion.
- ▶ DES-OFB and AES Digital encryption. Custom encryption schemes can be supported.
- ▶ Programmable function buttons and parameters allow radios to be tailored to exact requirements.
- ▶ Safety and emergency functions such as Lone Worker, Stun, GPS/Man Down and Emergency Alarm.
- ▶ Multi-vendor compatible accessory connector supports current generation or legacy accessories.
- ▶ AMBE+2 Vocoder for improved voice clarity.



# Specification

## General Specification

<b>Frequency Bands*</b>	AC (136 - 174 MHz); TU (400 - 480 MHz); UW (440 - 520 MHz)		
<b>Dimensions</b>	147 mm (H) x 63 mm (W) x 36 mm (D)		
<b>Weight</b>	408 g (with 3000 mAh battery)		
<b>Power Supply</b>	Li-ion 2200 mAh or 3000 mAh		
<b>Battery Life**</b>	>13 hours, high transmit power 3000 mAh battery, 90:5:5 duty cycle		
<b>Channel Stability</b>	<1.5 ppm		
<b>Display</b>	102 x 64 pixels		
<b>Switching Bandwidth</b>	Full band		
<b>Modulation</b>	Pre-emphasised FM, C4FM		
<b>Conformance</b>	EN 300 086, EN 300 113, EN 300 219, EN 300 489, EN 60950, AS4295, FCC, IC • P25CAP Compliant		
<b>Environmental Protection</b>	IP67		
<b>Environmental Standards</b>	<b>MIL-STD-810 F</b>	<b>Method</b>	<b>Procedure</b>
	Low Pressure (Altitude), Storage	500.4	I
	Low Pressure (Altitude), Operational	500.4	II
	High Temp, Storage	501.4	I
	High Temp, Operating	501.4	II
	Low Temp, Storage	502.4	I
	Low Temp, Operating	502.4	II
	Thermal Shock	503.4	I
	Solar Radiation	505.4	I (A2)
	Relative Humidity	507.4	
	Dust	510.4	I
	Sand	510.4	II
	General Vibration: Truck/trailer/tracked - restrained cargo	514.5	I Cat 4
	General Vibration: Minimum Integrity	514.5	I Cat 24
	Shock - Transit Drop	516.5	IV
<b>Operating Temperature</b>	-30 °C to +60 °C		

## Transmitter Specification

<b>Power Output</b>	3 levels programmable 0.5 - 5 W
<b>Audio Distortion</b>	<3 % at 1 kHz, 60% deviation
<b>Audio Frequency Response</b>	+1 dB to -3 dB of pre-emphasised 300 to 3000 Hz on 25 kHz Channel (300 to 2550 Hz on 12.5 kHz Channel)
<b>Tx/Rx switching time</b>	<25 ms
<b>Hum and Noise</b>	>40 dB (12.5 kHz); >45 dB (25 kHz)

## Receiver Specification

<b>Sensitivity</b>	>-117.5 dBm for 12 db SINAD >-119 dBm for 5% BER
<b>Selectivity</b>	>73 dB (25 kHz) >65 dB (12.5 kHz)
<b>Intermodulation</b>	>70 dB
<b>Audio Frequency Response</b>	+1 dB to -3 dB of de-emphasised 300 to 3000 Hz on 25 kHz Channel (300 to 2550 Hz on 12.5 kHz Channel)
<b>Audio Output</b>	500 mW into 16 $\Omega$ <5% distortion
<b>Blocking</b>	>95 dB at +/- 1 MHz
<b>Hum and Noise</b>	>40 dB (12.5 kHz); >45 dB (25 kHz)

## Analogue Conventional Operation

<b>Operation</b>	Single and two-frequency simplex 1000 channels 240 scan / vote groups (SRP9180), 200 channels (SRP9170)
<b>Signalling</b>	CTCSS, DCS, FFSK, DTMF, Sequential Tone (selcall)

## Analogue Trunked Operation

<b>Operation</b>	Two-frequency simplex in MPT 1327 trunked systems
<b>Number of Channels</b>	1024 trunked channels in 50 sub bands
<b>Network Capability</b>	<b>UK</b> – MPT1343 <b>Germany</b> – Chekker (Regionet 43) <b>France</b> – 3RP (CNET2424) <b>Netherlands</b> – Traxys (NL 1343) <b>Australia</b> – Multiplx, MPT1343

## P25 Operation

- P25CAP Compliant • 40 zones • 1500 channel pool
- 5 Trunking systems • Scanning • Voting
- DES OFB and AES Encryption\*\*\* • Individual Calls
- Emergency call • Analogue mode including scrambler,
- CTCSS, DCS, DTMF • AMBE+2 Vocoder

## Contact Us

**UK HQ**  
Field House  
Uttoxeter Old Road  
Derby  
DE1 1NH  
Tel: +44 (0) 1332 375 500  
info@simocowireless.com

**AUS HQ**  
1270 Ferntree Gully Rd  
Scoresby, VIC 3179  
Tel: +61 (0) 3 9730 3999  
Fax: +61 (0) 3 9730 3964  
inquiry.aus@simocowireless.com

[www.simocowirelessolutions.com](http://www.simocowirelessolutions.com)

